




Notes:

1. Material: PA66 UL94 V2;
2. Color: Natural;
3. Male (M2) Torques: ≥ 0.06 Nm;
Male (M2.5) Torques: ≥ 0.08 Nm;
Male (M3) Torques: ≥ 0.13 Nm;
Male (M4) Torques: ≥ 0.3 Nm;
Male (M5) Torques: ≥ 0.58 Nm;
Male (M6) Torques: ≥ 0.8 Nm;
Male (M8) Torques: ≥ 2.5 Nm;
4. RoHS Compliant.
5. The tolerance of "L" conform to the standard: DIN EN ISO 4017.

Part No. length	4.0	4.5	5.0	6.0	6.5	8.0	10.0	12.0	15.0	16.0	20.0	22.0	25.0	30.0	35.0	40.0	45.0	50.0	60.0	H	W
Article No.																					
GHHS-4017-M2-L	50586		50587	50588		50589	50590	50591		50592	50593		50594							1.4 $\pm$ 0.12	4.0 $^{+0}_{-0.18}$
GHHS-4017-M2.5-L	50595	50596	50597	50598		50599	50600	50601		50602	50603		50604							1.7 $\pm$ 0.12	5.0 $^{+0}_{-0.18}$
GHHS-4017-M3-L	50605		50606	50607		50608	50609	50610		50611	50612		50613	50614	50615	50616				2.0 $\pm$ 0.12	5.5 $^{+0}_{-0.18}$
GHHS-4017-M4-L	50617			50618		50619	50620	50621	50622	50623	50624		50625	50626		50627				2.8 $\pm$ 0.12	7.0 $^{+0}_{-0.22}$
GHHS-4017-M5-L				50458		50524	50525	50526		50527	50528		50529	50534		50535		50651		3.5 $\pm$ 0.15	8.0 $^{+0}_{-0.22}$
GHHS-4017-M6-L			50628	50629	50630	50631	50632	50633		50530	50531	50532	50533	50536		50537		50634	50635	4.0 $\pm$ 0.15	10.0 $^{+0}_{-0.22}$
GHHS-4017-M8-L						50714	50520	50521		50522	50434		50523	50636	50637	50638	50639	50640		5.3 $\pm$ 0.15	10.0 $^{+0}_{-0.27}$

Gecko International Co.

DATE

2022-8-26

DIMENSION

TOLERANCE

TITLE

HEXAGONAL HEAD SCREW

SCALE

FIT

L $\leq$ 4

$\pm$ 0.10

ARTICLE NO.

GHHS-4017

MOLD NO.

S0269/S0506

DRAW

JF

UNIT

MM

4 < L $\leq$ 15

$\pm$ 0.20

PART NO.

SEE TABLE

MATERIAL

SEE NOTES

DESIGN

JF

VERSION

A0

15 < L $\leq$ 50

$\pm$ 0.30

DWG NO.

E5039


COLOR

SEE NOTES

APPROVAL

FDL

VIEW



50 < L $\leq$ 100

$\pm$ 0.40